

PERFORMANCES HYDRAULIQUES -TS -TIC-TTI

ENROULEUR : OPTIMA 1015 DIAMETRE : ø 100 LONGUEUR : 260 M								REEL MACHINE : OPTIMA 1015 DIAMETER : ø 100 LENGTH : 260 M					
Turbine	ENROULEUR REEL MACHINE		CANON SR 150 GUN SR 150			esp.	surface	DOSE EN mm			DOSE IN mm		
Busse	pression	débit	p. canon	buse	portée	spacing	area	VITESSE EN m/h			WINDING SPEED IN m/h		
Nozzle	pressure	flow	p. gun	nozzle	distance	spacing	area	10	20	30	40	50	60
mm	bar	m ³ /h	bar	mm	m	m	has						
20	5.9 /6.7	33.4	4	22	43	66	1.9	51	25	17	13	10	8
20	6.5 /7.3	35.3	4.5	22	45	72	2.1	49	25	16	12	10	8
20	7.1 /7.9	37.1	5	22	46	72	2.1	52	26	17	13	10	9
20	7.6 /8.5	38.9	5.5	22	48.5	72	2.2	54	27	18	14	11	9
20	6.2 /7.0	40.4	4	24	45.5	72	2.1	56	28	19	14	11	9
20	6.8 /7.7	42.9	4.5	24	47.5	72	2.1	60	30	20	15	12	10
20	7.4 /8.3	45.2	5	24	49	78	2.3	58	29	19	14	12	10
20	8.1 /8.9	47.4	5.5	24	50.5	78	2.3	61	30	20	15	12	10
20	8.7 /9.5	49.6	6	24	51.5	78	2.3	64	32	21	16	13	11
20	9.3 /10.1	51.5	6.5	24	53	84	2.5	61	31	20	15	12	10
20	6.6 /7.4	48.3	4	26	48	72	2.1	67	34	22	17	13	11
20	7.2 /8.1	51.1	4.5	26	49.5	78	2.3	66	33	22	16	13	11
20	7.9 /8.7	53.9	5	26	51.5	78	2.3	69	35	23	17	14	12
20	8.6 /9.4	56.6	5.5	26	53	84	2.5	67	34	22	17	13	11
20	9.2 /10.0	59.1	6	26	54	84	2.5	70	35	23	18	14	12
20	7.1 /7.9	57.5	4	28	50.5	78	2.3	74	37	25	18	15	12
20	7.8 /8.6	61	4.5	28	52.5	84	2.5	73	36	24	18	15	12
20	8.5 /9.4	64.4	5	28	54	84	2.5	77	38	26	19	15	13
20	9.3 /10.1	67.6	5.5	28	55.5	84	2.6	80	40	27	20	16	13
TEMPS D'ENROULEMENT COMPLET EN HEURE TIME FOR COMPLETE WINDING IN HOUR								26.0	13.0	8.7	6.5	5.2	4.3

26/7/06